



# HF6 Single Phase



## Ah Battery

Code	Model	7 ÷ 8 h	10 ÷ 12 h	BOX	
HF6012020	12V / 20A	120÷140	160÷200	A	
HF6012025	12V / 25A	150÷175	200÷250	A	
HF6012030	12V / 30A	180÷210	240÷300	A	
HF6012040	12V / 40A	240÷280	320÷400	A	
HF6024020	24V / 20A*	120÷140	160÷200	A	
HF6024025	24V / 25A*	150÷175	200÷250	A	
HF6024030	24V / 30A*	180÷210	240÷300	A	
HF6024035	24V / 35A	210÷245	280÷350	A	
HF6024040	24V / 40A	240÷280	320÷400	A	
HF6036015	36V / 15A*	90÷105	120÷150	A	
HF6036020	36V / 20A*	120÷140	160÷200	A	
HF6036025	36V / 25A*	150÷175	200÷250	A	
HF6036030	36V / 30A	180÷210	240÷300	A	
HF6048015	48V / 15A*	90÷105	120÷150	A	
HF6048020	48V / 20A*	120÷140	160÷200	A	

Input 230Vac Supply 50/60Hz

Dimensions box A:  
190 (L) x 310 (H) x 130 (W)



### FEATURES:

- Input 230Vac  $\pm 10\%$  50/60Hz
- Standard color RAL 1028 (Yellow)
- Main cable and battery cables included
- no 8 charging characteristics available

### ON REQUEST:

(option to be required during the order):

- Input 110-240Vac Supply Extended range 50/60Hz  
Add to net price - **Only \* models**



### On request:

- **P/N 3451** Battery signalling cable L=1000mm

- **P/N 3452** Blocking relay for installation on board